

# tesa® 4089

General purpose carton sealing tape

## PRODUCT INFORMATION

### Product Description

tesa® 4089 PV6 is based on a 28µm-PP backing with a natural rubber adhesive.

### Main Application

Manual and automatic sealing of light and medium-range weight cartons.

### Technical Data

|                    |                |                       |         |
|--------------------|----------------|-----------------------|---------|
| ■ Backing material | PP film        | ■ Elongation at break | 150 %   |
| ■ Total thickness  | 46 µm          | ■ Tensile strength    | 41 N/cm |
| ■ Type of adhesive | natural rubber |                       |         |

### Properties

|                         |     |                      |     |
|-------------------------|-----|----------------------|-----|
| ■ Automatic application | yes | ■ Manual application | yes |
|-------------------------|-----|----------------------|-----|

For latest information on this product please visit <http://l.tesa.com/?ip=04089>

Page 1 of 1 / As of 02/25/15

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

tesa SE  
A Beiersdorf Company

[www.tesa.com](http://www.tesa.com)

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
[www.tesatape.com](http://www.tesatape.com)

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
[www.tesa-asia.com](http://www.tesa-asia.com)

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.