

# tesa® 4289

Heavy duty tensilised strapping tape

## PRODUCT INFORMATION

### Product Description

tesa® 4289 is a heavy duty tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa® 4289 features very high tensile strength with low elongation at the same time. The product is highly abrasion resistant.

### Main Application

Surface protection of glass, bundling of heavy steel pipes, palletising, end tabbing of light gauge rolled steel and finished metals.

### Technical Data

■ Backing material	MOPP	■ Adhesion to steel	5.5 N/cm
■ Total thickness	150 µm	■ Elongation at break	35 %
■ Type of adhesive	natural rubber	■ Tensile strength	375 N/cm

### Properties

■ Residue free removal	yes	■ No discolouration	yes
------------------------	-----	---------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=04289>

Page 1 of 1 / As of 02/25/15

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

tesa SE  
A Beiersdorf Company

[www.tesa.com](http://www.tesa.com)

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
[www.tesatape.com](http://www.tesatape.com)

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
[www.tesa-asia.com](http://www.tesa-asia.com)

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.