

tesa® 60952

Anti Slip safety solution

PRODUCT INFORMATION

Product Description

The application area for tesa® Anti Slip Professional range is everywhere safe footing is required. Anti Slip transparent is the ideal protection to prevent from skidding and therefore helps to avoid accidents in the job related. Very good adhesion of the product is suitable for demanding surfaces such as factory floors, industry areas etc. The strong and durable adhesive coating secures a high Anti Slip effect of up to 1- 2 years in normal use areas. The Anti Slip tapes are hand tearable and no shrinkage occurs after application.

Main Application

Everywhere safe footing is required.

Technical Data

■ Backing material	PVC film	■ Adhesion to steel	10 N/cm
■ Total thickness	810 µm	■ Elongation at break	200 %
■ Type of adhesive	acrylic		

Properties

■ Hand tearability	+	■ Resistance to chemicals	+
■ Easy to remove	yes	■ Salt water resistant	+
■ Suitable for die cutting	yes		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=60952>

Page 1 of 1 / As of 02/26/15

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.