

tesa® 4541

Conformable uncoated cloth tape

PRODUCT INFORMATION

Product Description

tesa® 4541 is a highly tear-resistant uncoated cloth tape. It is based on a 145 mesh rayon fabric backing and natural rubber adhesive. tesa® 4541 is a very flexible and conformable tape convenient for a wide range of applications.

Features:

- good adhesion even on rough and oily surfaces
- adapts to uneven surfaces without creasing
- easy to write on, ideal marking tape
- very high tensile strength
- smooth and conformable
- · available in 5 colours: black, white, grey, red, brown

Main Application

- Manual and machine driven closure of heavy cartons, buckets and tins
- Sealing of film containers, junction boxes and gap closures
- Bundling of bars, rods and cables
- Cable harnessing
- Securing of edges
- Reinforcing of book covers
- Fixing of plastic clips to cable tubes
- Reinforcing of hockey sticks
- Various applications in animal health care for bandaging large and small animals

Technical Data

Tensile strength Backing material uncoated cloth 90 N/cm Total thickness Temperature resistance (30 min) 130 °C 270 µm

Type of adhesive natural rubber Mesh 145 count per square inch

Surface finish Adhesion to steel 3.6 N/cm matt Elongation at break 16 %

Properties

Easy to write on yes Abrasion resistance

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

Complies with LV 312-1 Dialectric strength.

For latest information on this product please visit http://l.tesa.com/?ip=04541

Page 1 of 1 / As of 02/25/15

tesa SE

Quickbornstraße 24 20253 Hamburg

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 Germany United States of America Singapore Communication (Aug.) United States of America Singapore Communication (Aug.) Phone: +49 (40) 4909 101 Phone: +1 (704) 554 0707 Tel: +65 6697 9888 Fax: +1 (704) 553 5634 Fax: +65 6659 6390 Fax: +65 6659 Fax: +65 United States of America www.tesatape.com www.tesa-asia.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive #04-01 The Metropolis Tower 1

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.