

tesa® 52330

Plate mounting in flexographic printing, especially corrugated board postprint

PRODUCT INFORMATION

Product Description

tesa® 52330 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Adhesive properties

- High adhesive coating weight to ensure the secure mounting of plates that have been "back ground"
- The adhesive properties also allow secure vertical storage of mounted plates

Backing properties

- tesa® 52330 is very flexible, yet stable, due to its fabric backing material and therefore are ideally suited for plates in corrugated board postprint
- The stability of the backing also ensures that mounted plates can be stored vertically

Additional properties

- tesa® 52330 has a creped paper liner to prevent the formation of air bubbles during plate mounting

Main Application

tesa® 52330 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Technical Data

■ Backing material	cloth	■ Type of adhesive	natural rubber
■ Thickness category	380 µm	■ Type of liner	creped paper

For latest information on this product please visit <http://l.tesa.com/?ip=52330>

Page 1 of 1 / As of 02/26/15

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.