



Product Data Sheet

Date March 2011
Supersedes: June 1997

Product Description This 3M™ Double Coated Tape 9195 has a robust adhesive tape construction. This tape has a versatile use as mounting tape. The adhesive bond to different materials such as plastics, metal, paper, cardboard, fabric etc.

Key Features 3M™ 9195 is a double coated tape with different adhesive on each side of the carrier. One side has a high tack and the other side has a lower tack, this feature is often useful in fairs. This double coated tape bonds carpet to concrete or gymnastic floors and can be removed without any residue. The acrylic adhesive is resistant to plasticizers.

Construction

	9195
Thickness (PSTC-33) Tape	0,13 mm
Release Liner	Silicon paper
Tape Colour	Yellow
Adhesive Type	Hot-melt Acrylic
Adhesive Carrier	Polypropylene film

Performance Characteristics

Adhesion to Stainless Steel	Inner side of the tape 5N/cm Liner side of the tape 1,5N/cm
Temperature Performance	60°C
Tensile Strength e.g. PSTC-31	20N/cm
Elongation at Break e.g. PSTC-31	500%

Storage	Store 3M 9195 at room temperature or refrigerate for maximum shelf life.
Shelf Life	3M 9195 has a shelf life of e.g. 12 months from date of dispatch by 3M when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity
Precautionary Information	Refer to product label and Material Safety Data Sheet for health and safety information before using the product. For information please contact your local 3M Office. www.3M.com
For Additional Information	To request additional product information or to arrange for sales assistance, call 08-92 22 50 Address correspondence to: 3M Svenska AB Bollstanäsvägen 3 191 89 Sollentuna (Sweden)
Important Notice	All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method or application. All questions of liability relating to this product are governed by the terms of the sale subject, where applicable, to the prevailing law

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations

3M is a trademark of the 3M Company.



3M Svenska AB
Industri

Bollstanäsvägen 3
191 89 Sollentuna

Tel: 08-92 22 50

Fax: 08-92 22 88

E-post: kundservice@mmm.com

www.3M.se/tejp