

# tesa® 6012

Manual bench dispenser

## PRODUCT INFORMATION

### Product Description

The tesa® 6012 is a universal dispenser for tesa® packaging tapes in 66 m rolls, up to 50 mm width. The dispenser can be filled with either one wide roll or two narrow rolls of tape. The tesa® 6012 dispenser is an all-purpose dispenser for production and warehouse use, for sealing small packages and for taping wrapping paper. As the dispenser can accommodate two rolls of tape, it can be used with different tesa® tape at the same time (e.g. different widths or colours).

### Main Application

The dispenser can be fastened securely with the supplied clamp or with screws on the packing table (four screw holes are prepared). The tape is pulled off and cut along the serrated blade.

### Technical Data

Type of tape	single-sided	Weight	600 g
Application purpose	packaging	Max. roll diameter	145 mm
Length	170 mm	Max. core diameter	3 inch
Width	125 mm	Type of applicator	table
Height	60 mm	Max. roll width	50 mm
Mode of drive	manual		

For latest information on this product please visit <http://l.tesa.com/?ip=06012>

Page 1 of 1 / As of 02/25/15

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

tesa SE  
A Beiersdorf Company

[www.tesa.com](http://www.tesa.com)

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
[www.tesatape.com](http://www.tesatape.com)

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
[www.tesa-asia.com](http://www.tesa-asia.com)

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.