

tesa® 6300

Dispenser ECONOMY for packaging tapes

PRODUCT INFORMATION

Product Description

The tesa® 6300 hand dispenser is a good value dispenser for professional sealing of all kind of tesa® packaging tapes in packaging and production areas. The dispenser has a tension control so that even easy unwinding tesa® tapes can be used without difficulty. The blade is covered with a top to prevent injuries.

Main Application

Place the dispenser on the carton and pull it towards yourself. The contact roller presses the tape down firmly as it is applied from the roll. The tape is cut by the serrated blade by tilting the dispenser. The cut end of the tape is pressed to the carton by the flexible application plate. Threading: The tesa® roll is put on the tape wheel such that the adhesive side of the tape faces the handle. Pull the end of the tape between the tape guide roller and the metal plate until the tape is free of wrinkles.

Technical Data

■ Type of tape	single-sided	■ Weight	400 g
■ Application purpose	packaging	■ Max. roll diameter	120 mm
■ Length	220 mm	■ Max. core diameter	3 inch
■ Width	65 mm	■ Type of applicator	hand
■ Height	150 mm	■ Max. roll width	50 mm
■ Mode of drive	manual		

For latest information on this product please visit <http://l.tesa.com/?ip=06300>

Page 1 of 1 / As of 02/25/15

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.