

tesa® 4173 PV2

Soft PVC tape for standard wrapping

PRODUCT INFORMATION

Product Description

tesa® 4173 PV2 is a PVC film wire harness tape with an acrylic adhesive.

Major Features:

- Temperature resistance 105°C/3000h
- Flexible
- Handtearable

Color: Black

Main Application

tesa® 4173 is designed for the passenger compartment for standard wrapping up to a temperature class of 105°C.

Technical Data

■ Backing material	PVC film	■ Temperature resistance (3000h)	105 °C
■ Total thickness	128 µm	■ Abrasion resistance (10mm mandrel)	Class A (acc. to LV312)
■ Type of adhesive	acrylic	■ Abrasion resistance (5mm mandrel)	Class A (acc. to LV312)
■ Adhesion to steel	1.8 N/cm	■ Flame resistance as composite	Class B (acc. to LV312)
■ Elongation at break	250 %	■ Noise damping (decibel)	Class A (acc. to LV312)
■ Tensile strength	30 N/cm	■ Dielectric breakdown voltage	7000 volt
■ Temperature Resistance MIN	-25 °C		

Additional Info

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 33 m

- Most combinations of width and length are possible
- Further dimensions are available upon request

- Standard core diameter: 38 mm

For latest information on this product please visit <http://l.tesa.com/?ip=04173>

Page 1 of 1 / As of 02/25/15

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

www.tesa.com

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
www.tesatape.com

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
www.tesa-asia.com

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.