

# tesa® 52310

For the mounting of photopolymer plates, also on compressible sleeves

## PRODUCT INFORMATION

### Product Description

tesa® 52310 (transparent), tesa® 52315 (yellow), tesa® 52320 (white) and tesa® 52325 (pink) are a range of tesaprint® plate mounting solutions, each of a different thickness category.

The unwind characteristics of all four tapes offer easier tape mounting. The structured PP-liner also prevents the formation of air pockets when plate mounting. Plates are easily repositioned during mounting as the full adhesion of the tape only becomes effective during the print run.

The high adhesion and good shear resistance of these tapes ensure that there is no plate movement or edge lift problems, even at high speeds and on extended print runs. On demounting, there are no adhesive residues on the plate or the cylinder.

tesa® 52310 is also especially well suited to the mounting of photopolymer plates on compressible sleeves.

### Main Application

The mounting of photopolymer plates in flexographic printing, especially on compressible sleeves

### Technical Data

■ Backing material	PVC film	■ Type of adhesive	natural rubber
■ Thickness category	100 µm	■ Type of liner	PP

For latest information on this product please visit <http://l.tesa.com/?ip=52310>

Page 1 of 1 / As of 02/25/15

#### tesa SE

Quickbornstraße 24  
20253 Hamburg  
Germany  
Phone: +49 (40) 4909 101

tesa SE  
A Beiersdorf Company

[www.tesa.com](http://www.tesa.com)

#### tesa tape inc.

5825 Carnegie Boulevard  
Charlotte, N.C. 28209  
United States of America  
Phone: +1 (704) 554 0707  
Fax: +1 (704) 553 5634  
[www.tesatape.com](http://www.tesatape.com)

#### tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive  
#04-01 The Metropolis  
Tower 1  
Singapore 138588  
Tel: +65 6697 9888  
Fax: +65 6659 6390  
[www.tesa-asia.com](http://www.tesa-asia.com)

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.